Dynapac CC1200 Plus (T4f)

Double drum vibratory rollers





Technical data

\$,	Masses		
	Max. operating mass		6,000 lbs
	Operating mass (incl. ROPS)	5,700 lbs	
	Module mass (front/rear)	2,800 lbs/2,900 lbs	
0	Propulsion		
	Speed range		0-6 mph
	Vertical oscillation		±10°
	Theor. gradeability		43 %
₩	Compaction		
	Centrifugal force		4,720 /8,660 lb
	Nominal amplitude		0.020 in
	Static linear load (front/rear)		59 /63 lbs/in
	Vibration frequency		2,940 /4,140 vpm
	Water tank		42 gal

Engine						
Manufacturer/Model		Kubota D1703-M-DI-E4B (T4f)				
Туре		Water cooled				
Rated power, SAE J19	995	25 hp @ 2,200 rpm				
Fuel tank capacity		13 gal				
Hydraulic system						
Driving	Axial piston pump with variab displacemer Radial piston motors (2) with consta displacemer					
Vibration	Gear pump/motors with constant displacement.					
Steering	Gear pump with constant displacement.					
Service brake	Hydrostatic in forward and reverse lever.					
Parking/Emergency	Fa	ilsafe multidisc brake in both drums.				

Find us locally at www.atlascopco.com


brake


We reserve the right to change specifications without notice. Photos and illustrations do not always show standard versions of machines. The above information is a general description only, all informations are supplied without liability.

Dynapac CC1200 Plus (T4f)

Double drum vibratory rollers

Technical data





Dimensions	
A. Wheelbase	68 in
B. Width	52 in
C. Curb clerance	22 in
D. Drum diameter	27 in
H1. Height, with ROPS/cab	104 in
H2. Height, w/o ROPS/cab	69 in
K. Ground clearance	7 in
L. Length	94 in
O1. Overhang, right	2 in
O2. Overhang, left	2 in
R1. Turning radius, outside	150 in
R2. Turning radius, inside	102 in
S. Drum shell thickness	0.5 in
W. Drum width	47 in
α. Steering angle	±30°

Equipment package		
CC Plus Package	Included	Optional
Backup alarm	•	
Brake release	•	
CE sign	•	
Driving lights, right or left handed		
Dual arm rest	•	
Dual forward/reverse control		
Dual frequency		
Flow divider		
Foldable ROPS incl. 3" seatbelt		
Rotating beacon	•	
Slideable comfort seat	•	
Slideable lux seat		
Spring loaded scrapers	•	
Sprinkler timer	•	
Vibr. shut off, front and rear drum	•	
Working lights		

Standard equipment

Backup alarm, Brake release, CE Sign, Dual arm rest, Foldable ROPS incl. seatbelt, Rotating beacon, Sprinkler timer, Slideable comfort seat, Vibration shut off (front and reardrum), Working lights



Optional equipment

Biodegradable hydraulic fluid, Fire extinguisher, Foot rest, Hearing protectors, Licence plate light, Rear view mirror, traffic view, Service kit 50/500/1000H, Side direction lights (driving lights required), Slow moving vehicle sign, Special color (one or two), Tool set, Towing eyelet, Water tank cover (lockable)

Find us locally at www.atlascopco.com

We reserve the right to change specifications without notice. Photos and illustrations do not always show standard versions of machines. The above information is a general description only, all informations are supplied without liability.

