## **Dynapac CC1300**

## Double drum vibratory rollers





#### **Technical data**

| Masses                      |                 |
|-----------------------------|-----------------|
| Max. operating mass         | 8,900 lbs       |
| Operating mass (incl. ROPS) | 8,600 lbs       |
| Module mass (front/rear)    | 4,200/4,400 lbs |

| Propulsion           |         |
|----------------------|---------|
| Speed range          | 0-6 mph |
| Vertical oscillation | ±10°    |
| Theor. gradeability  | 37 %    |

| Compaction                      |              |
|---------------------------------|--------------|
| Centrifugal force               | 7,400/       |
| Nominal amplitude               | 0.020 in     |
| Static linear load (front/rear) | 82/86 lbs/in |
| Vibration frequency             | 3,120/       |
| Water tank                      | 53 gal       |

| Engine                 |                      |
|------------------------|----------------------|
| Manufacturer/Model     | Kubota V2203-M (T4i) |
| Туре                   | Water cooled         |
| Rated power, SAE J1995 | 44 hp @ 2,600 rpm    |
| Fuel tank capacity     | 13 gal               |


| Hydraulic system        |   |
|-------------------------|---|
| Driving                 | Axial piston pump with variable<br>displacement.<br>Radial piston motors (2) with constant<br>displacement. |
| Vibration               | Gear pump/motors with constant displacement.  |
| Steering                | Gear pump with constant displacement.   |
| Service brake           | Hydrostatic in forward and reverse lever.   |
| Parking/Emergency brake | Failsafe multidisc brake in both drums.   |


# Dynapac CC1300

### Double drum vibratory rollers



#### **Technical data**





| Dimensions                  |        |
|-----------------------------|--------|
| A. Wheelbase                | 76 in  |
| B. Width                    | 57 in  |
| C. Curb clerance            | 24 in  |
| D. Drum diameter            | 32 in  |
| H1. Height, with ROPS/cab   | 108 in |
| H2. Height, w/o ROPS/cab    | 73 in  |
| K. Ground clearance         | 10 in  |
| L. Length                   | 107 in |
| O1. Overhang, right         | 2 in   |
| O2. Overhang, left          | 2 in   |
| R1. Turning radius, outside | 167 in |
| R2. Turning radius, inside  | 116 in |
| S. Drum shell thickness     | 0.6 in |
| W. Drum width               | 51 in  |
| α. Steering angle           | ±30°   |



Standard equipment

Backup alarm, Foldable ROPS incl. 3" seatbelt, Working lights



Optional equipment

Biodegradable hydraulic fluid, Fire extinguisher, Foot rest, Hearing protectors, Licence plate light, Rear view mirror (traffic view), Service kit 50/500/1000H, Side direction lights (driving lights required), Slow moving vehicle sign, Special color (one or two), Tool set, Towing eyelet, Water tank cover (lockable)